

PERFORMANCE MEASUREMENT TECHNOLOGY AIR STREAM FAN

AUXILIARY COMPONENT BLOWER VP 160009



AUXILIARY COMPONENT BLOWER VP 160009

The moving auxiliary component blower is used for additional, targeted cooling of the intercooler, exhaust manifold, oil cooler and other areas of the vehicle. Because of its retractable and height-adjustable suspension, all sensitive vehicle areas can be easily reached and individually cooled.

PRODUCT DETAILS/ACCESSORIES

Description:

- Extendible height-adjustable brackets for specific cooling of sensitive vehicle areas
- Additional targeted cooling of intercoolers, exhaust manifolds,

- oil coolers and other areas
- Varnished with high-quality powder coating: Window Grey, RAL 7040

TECHNICAL DATA

Volumetric flow	540 m ³ /h
Max. outflow speed at the nozzle	140 km/h
Motor power	2.2 kW
Fuse	16 A
Power supply	3/N/PE 400 V 50 Hz
Total weight	60 kg
Dimensions (H x W x L)	1150 x 470 x 1650 (max. 2650) mm
Max. projection	2000 mm

ACCESSORIES

SUPPLEMENTARY CHARGES

VT 998183	Internal transport -SOUTH AIR Cooling fan
VT 998184	Internal transport -NORTH AIR Cooling fan