

LIFTING TECHNOLOGY

TWO POST LIFT

MA STAR 3.5 A STOCK
VP 251230



MA STAR 3.5 A STOCK

VP 251230

The 5-star lift MA STAR 3.5 A, which features stable torsion-resistant columns of rolled H-section steel, lifts cars and vans of up to 3.5 t. Its 45° rotated columns allow a wide opening angle for vehicle doors. The two post lift guarantees triple safety thanks to its spindle nut package, patented "giraffe" nut breakage detection and motor brake. The MA STAR also impresses with its straightforward plug and play commissioning as well as its intuitive, LED-based operation.

STOCK version - available ex stock.

PRODUCT DETAILS/ACCESSORIES

STOCK version - available ex stock

- RAL 7040 -

Description:

- Load capacity 3500 kg
- triple safety
- Columns turned by 45° for wide opening at the vehicle
- Asymmetrical support arms
- Short support arms swivelling 180°
- Variable installation width
- High-quality powder coating:
 - Window grey, RAL 7040 (columns)

- Anthracite grey, RAL 7016 (lifting carriages, support arms)

Scope of delivery:

- 2 asymmetrical columns with operating unit
- 4 asymmetrical support arms (2 double, 2 single telescopic)
- Support disc plug-in system
- Cable bridge
- Spindle oil (0.5 l)
- Operating instructions
- CE Declaration of Conformity
- Transport packaging

TECHNICAL DATA

Load capacity CE	3500 kg
Max. lifting height	1995 mm
Lifting / lowering time (depends on load)	approx. 40/40 s
Bottom clearance of the support arms	100 mm
Adjustment range, support disc	80 - 110 mm
Extension range, short support arms	630 - 1240 mm
Extension range, long support arms	920 - 1490 mm
Overall width*	3592 mm
Outside base plates*	3351 mm
Outside columns* 3242 mm
Inside columns*	2660 mm
Drive-through width	2300 - 2450 mm
Column height	2943 mm
Max. overall height (with cable bridge)	4499 mm
Drive power	2 × 3.0 kW
Power supply	3/N/PE 400 V 50 Hz
Fuse	C16 A

LIFTING TECHNOLOGY TWO POST LIFT

MA STAR 3.5 A STOCK
VP 251230



TECHNICAL DATA

Weight	650 kg
Packaging dimensions (L x W x H)	2900 x 1100 x 710 mm
Required concrete quality	C 20/25
Required thickness of concrete slab w/o screed	min. 180 mm

ACCESSORIES

ACCESSORIES COLUMNS

VZ 990488	Power Set mounted to Operating Column
VZ 990500	Power Set mounted to Operating Column
VZ 971590	Additional Operating Panel at Opposite Column MA STAR 3.5 incl. emergency-stop button
VZ 990489	Power Set mounted to Opposite Column
VZ 990501	Power Set mounted to Opposite Column
VZ 990504	Power Set mounted to Operating Column
VZ 990505	CE Stop beeper volume adjustable -EXTRA CHARGE-
VZ 990503	Socket combination Energy box
VZ 971591	Holder for Pneumatic Air Wrench and 6 Sockets
VZ 971592	Document Holder, suitable for column/wall mounting (1 pcs.)
VZ 971593	Holding Device for 2 Support Plate Extensions, can be mounted to Lift (1 pcs.)
VZ 971224	Holding Device for 2 Support Plate Extensions, can be mounted to Wall (2 pcs.)
VZ 990493	LED light (1 pce) pluggable
VZ 971607	Door stop (2 pcs) on lifting carriage for vehicles with low doors
VZ 971615	Perforated plate modules in in L-shape for Hoffmann GARANT Easyfix

ACCESSORIES SUPPORT ARMS

VZ 971346	Special Support (4 pcs) for AUDI TT/TTS/TT RS, suitable f. Lifting Points of Vehicle Jack
VZ 971247	Support Plates for VOLVO external diameter 100 mm plug-in system- (4 pcs.)
VZ 971220	Support Plate Extension 50 mm, galvanized, (2 pcs.) Diameter of supports 35 mm
VZ 971221	Support Plate Extension 100 mm galvanized (2 pcs.) Diameter of supports 35 mm
VZ 971222	Support Plate Extension 150 mm galvanized (2 pcs.) Diameter of supports 35 mm
VZ 971223	Support Plate Extension 200 mm galvanized (2 pcs.) Diameter of supports 35 mm
VZ 975050	Non-skid device for vehicles with longitudinal frame up to 100 mm width (2 pcs)

VZ 971649	Strap attachment on support arm thread for tilt protection
VZ 971227	Special Prism Support for MB G-Class w/o Tread Plate Plug-In System - (4 pcs.)
VZ 971520	Special Prism Support for MB G-Class with Tread Plate Plug-In System - (4 pcs.)
VZ 971539	Storage Tray MAHA stainless steel, magnetic for small parts, (2 pcs)

ACCESSORIES SAFETY SYSTEMS

VZ 971104	Light Barrier Safety Device to avoid Contact with Ceiling
-----------	--

FURTHER ACCESSORIES

VZ 971600	Drilling template for MA STAR 3.5 A
VZ 971606	Set-up device for MA STAR 3.5 A/S
VZ 971594	Add. Ground Plates (2 pcs) for
VZ 971605	CEE coupler 16A for on-site connection
VZ 990490	Socket for inground wiring

SUPPLEMENTARY CHARGES

VT 998047	Transport Zweisäulen-Hebebühne MAHA direkt durch Werksverkehr bis 3500 kg Tragl. (1-4 Stück)
VT 998048	Transport Zweisäulen-Hebebühne MAHA direkt durch Werksverkehr bis 3500 kg Tragl. (4-9 Stück)
VT 998049	Transport Zweisäulen-Hebebühne MAHA direkt durch Werksverkehr bis 3500 kg Tragl. (ab 10 St.)
VM 995024	Installation costs Two-post lift, electromechanical load capacity 3500 kg
VM 996232	Montagekosten Energieset
VM 996233	Montagekosten zusätzliche Bedieneinheit an Gegensäule
VM 996072	Install. Charges f. Ceiling Light Barrier -T&M Basis
VM 999079	Install. material Injection system for MA STAR 3.5 A
VM 999082	Install. material Injection system for MA STAR 3.5 A
VM 999054	Install. material Injection system for MA STAR 3.5 A/S
VM 999081	Injection mortar Cartridge 500 ml (1 pce)